

FLOS

05.2601.40 White/Black

Light Shadow Pro Ø60 Surface Spot

Designed by Flos Architectural, 2022




LED - LED array - 15W - 966lm - 2700K - CRI> 90 - Beam° 15

Luminaire with low glare for surface installation. Integrated 220-240 V power supply. For dimmable versions, please refer to the recommended dimmers in the product data sheet available on the website. IP54 watertightness.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Surface
Environment	Indoor Outdoor damp location
Light source type	LED
LED type	LED array
Lamp category	LED
Number of heads	1
Power (W)	15
System flux (lm)	966

Physical

Colour	White/Black
Orientation	Fixed
Spot diameter (mm)	65
Length (mm)	65
Net weight (kg)	0.37
IP	54

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)



Ecodesign and Energy Labelling




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Schematic light drawing



Beam Angle: 15°

h(m)	E(lx)	D(m)
1	11213	0.27
2	2803	0.54
3	1246	0.82
4	701	1.09
5	449	1.36

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Rf fidelity index	93
Rg gamut index	99
LED Life / Failure Ratio	L90B10_33.000_Tc=85°C
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15

Electrical

Insulation class	I
Frequency (Hz)	50-60
Main voltage (Vac)	220
Alternating current voltage (Vac)	220-240V~
Forward voltage (V)	36.5
LED current (mA)	300
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable